Míele

PWM 920 [SI DV DD]

Professional washing machine, steam heating (indirect) with detergent drawer, M Touch Pro Plus – freely programmable.



- Drum volume 6.36 (180) ft³ (I), load size 45 (20.0) lb (kg)
- Top cleaning & consumption values innovative Miele technology
- Ideal operation thanks to touch color display M Touch Pro Plus
- Simple and safe operation thanks to automatic door lock
- Connected for the future using LAN and WiFi

EAN: 4002516445203 / Material number: 11803340 / Old Material Number: 51920031NAM

Old Material Number: 51920031NAM	
Construction type and design	
Design	Front loader
Product line	Performance Plus
Front	Stainless Steel
Control panel color	Stainless Steel
Maximum load with a load ratio of 1:9 in lbs	45 (20.0)
Load ratio	1:9
Load in lbs	45 (20.0)
Drum volume in cubic feet (I)	6.36 (180)
Door opening [Ø] in in.(mm)	16 3/8 (415)
Door opening angle in degrees	180
Door hinging	right
Automatic door lock	•
Innovative suds container	•
Maintenance-free motor with frequency converter	•
Patented stainless steel honeycomb drum 2.0	•
Application	
Suitable for the hotel and catering industry	•
Suitable for senior living facilities	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centers	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemical industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks and holiday complexes	•
Suitable for public/community care facilities	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/kg	6.20
Specific energy consumption for cold water connection in kWh/lb	0.14
Specific water consumption for hot water connection in I/kg	5.90
Specific energy consumption for hot water connection in kWh/lb	0.06
Water consumption for cold water connection in I	124.0
Energy consumption for cold water connection in kWh	2.91
·	

Miele

PWM 920 [SI DV DD]

Professional washing machine, steam heating (indirect) with detergent drawer, M Touch Pro Plus – freely programmable.



EAN: 4002516445203 / Material number: 11803340 / Old Material Number: 51920031NAM	
Energy consumption for cold water connection in Mops standard program in kWh	3.21
Program duration in minutes with cold water connection	52
Water consumption for hot water connection in I	118.0
Water consumption for hot water connection in Mops standard program in gal	222.6
Energy consumption for hot water connection in kW	1.20
Energy consumption for hot water connection in Mops standard program in kWh	1.66
Program duration in minutes with hot water connection	44
Water consumption in ECO program for cold water connection in I	116.0
Energy consumption in ECO program for cold water connection in kWh	1.90
Program duration in minutes for ECO program with cold water connection	34
Water consumption in ECO program for hot water connection in I	114.0
Energy consumption in ECO program for hot water connection in kWh	0.60
Program duration in minutes for ECO program with hot water connection	33
Program runtime in minutes for Mops standard program with cold water connection	53
Program runtime in minutes for Mops standard program with hot water connection	50
Residual moisture with cold rinse in %	48
Residual moisture with cold finse in 70	
Residual moisture with cold finise in %	44
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in %	44 25
Residual moisture with hot rinse in %	44 25 1075
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor	44 25
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours	44 25 1075
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control	44 25 1075 462 30000
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system	44 25 1075 462 30000 M Touch Pro Plus
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability	44 25 1075 462 30000 M Touch Pro Plus Freely programmable
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h	44 25 1075 462 30000 M Touch Pro Plus
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h Countdown indicator	44 25 1075 462 30000 M Touch Pro Plus Freely programmable
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control System Programmability Max. delay start in h Countdown indicator Program sequence indicator	44 25 1075 462 30000 M Touch Pro Plus Freely programmable
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language	44 25 1075 462 30000 M Touch Pro Plus Freely programmable
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language Option to enter weight prior to start of program	44 25 1075 462 30000 M Touch Pro Plus Freely programmable
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard/target group programs	44 25 1075 462 30000 M Touch Pro Plus Freely programmable
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard/target group programs Basic programmes	44 25 1075 462 30000 M Touch Pro Plus Freely programmable
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard/target group programs Basic programmes Dispensing	44 25 1075 462 30000 M Touch Pro Plus Freely programmable Can be selected freely • • •
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard/target group programs Basic programmes Dispensing Detergent dispenser drawer	44 25 1075 462 30000 M Touch Pro Plus Freely programmable Can be selected freely • • • • • 3 compartments
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard/target group programs Basic programmes Dispensing Detergent dispenser drawer Maximum number of connections for liquid dispenser pumps [number]	44 25 1075 462 30000 M Touch Pro Plus Freely programmable Can be selected freely • • • • 3 compartments 12
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard/target group programs Basic programmes Dispensing Detergent dispenser drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor	44 25 1075 462 30000 M Touch Pro Plus Freely programmable Can be selected freely • • • • • 3 compartments
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard/target group programs Basic programmes Dispensing Detergent dispenser drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection	44 25 1075 462 30000 M Touch Pro Plus Freely programmable Can be selected freely • • • • 3 compartments 12
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard/target group programs Basic programmes Dispensing Detergent dispenser drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Type of heating	44 25 1075 462 30000 M Touch Pro Plus Freely programmable Can be selected freely • • • • Indirect steam
Residual moisture with hot rinse in % Residual moisture when processing cleaning cloths in % Spin speed in rpm g factor Tested operating hours Control Control system Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language Option to enter weight prior to start of program Standard/target group programs Basic programmes Dispensing Detergent dispenser drawer Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection	44 25 1075 462 30000 M Touch Pro Plus Freely programmable Can be selected freely • • • • 3 compartments 12



PWM 920 [SI DV DD]

Professional washing machine, steam heating (indirect) with detergent drawer, M Touch Pro Plus – freely programmable.

EAN: 4002516445203 / Material number: 11803340 /

Old Material Number: 51920031NAM

Total connected load in kW	3.10
Fuse rating in A	20
Water connection/drainage	
Cold water [number]	3 x 1/2" hose w/ 3/4" union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Hard water (optional) [number]	2 x 1/2" w/ 3/4" union
Dump valve	DN 70
Steam connection	
Steam connection	2 x ½"
Dimensions and weight	
External dimensions, net height in inches	57 1/8 (1450)
External dimensions, net width in inches	36 7/16 (924)
External dimensions, net depth in inches	41 1/2 (1054)
External dimensions, gross height in inches	62 7/16 (1585)
External dimensions, gross width in inches	47 11/16 (1210)
External dimensions, gross depth in inches	44 1/2 (1130)
Net weight in lbs.(kg)	893 (405.0)
Gross weight in lbs.	944 (428)
Maximum floor load in N	5721
Emission values	
Emissions – sound pressure at workplace	67 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	6.48
Features	
Patented preliminary drainage	•
Patented cleaning cloth program	•
3-dimensional imbalance monitoring	•
Disinfection rinse	•
Efficient scoop-and-ladle ribs	•
EcoSpeed	•
Spring-in-spring system	•
Temperature monitoring	•
Automatic load control Plus	•
Volumetric flow meter (optional)	•
Add laundry	•
Program selection via color frame	•
Efficient fast spin cycle	•
Emergency shut off	•
Appliance-independent accessories	٠
Efficiency and sustainability	
Recycling rate in %	92
Connection options	
Payment system (optional)	<u> </u>
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
Water recovery (optional)	<u> </u>
LAN	<u> </u>
WiFi	<u> </u>

Míele

PWM 920 [SI DV DD]

Professional washing machine, steam heating (indirect) with detergent drawer, M Touch Pro Plus — freely programmable.



EAN: 4002516445203 / Material number: 11803340 / Old Material Number: 51920031NAM

Connector Box	•
Capacities	
Respirator masks [number]	15
Helmets [number]	5
Overalls [number]	3
Over jackets [number]	5
Chemical protection overalls [number]	2
Synthetic duvets [number]	2
Synthetic pillows [number]	4
Feather duvets [number]	2
Feather pillows [number]	4
Cloths, 22 g/0.8 oz[number]	456
Cotton mops, 40 cm/15.7 in[number]	106
Cotton mops, 50 cm/19.7 in[number]	91
Microfibre mops, 40 cm/15.7 in [number]]	167
Microfibre mops, 50 cm/19.7 in [number]	117
Mops, office, 100 g [quantity]	200
Mops, stairway, 150 g [quantity]	130
Summer horse blankets [number]	3
Standards, test certificates, and symbols	
Splash protection IPX4	•
c ETL US	•
Complies with Machinery Directive 2006/42/EC	•