

## PDR 914 [EL]

Professional vented dryer, electric heating

with programmable M Touch Pro controls for the maximum in flexibility.



- Drum volume 8.83 (250.00) ft<sup>3</sup> (l), load size 23 (10.0) lb (kg) – 30 (13.5) lb (kg)
- Unique, gentle fabric care – patented honeycomb drum
- Maximum energy efficiency thanks to Air Recycling Flex
- Precision drying of all fabrics – PerfectDry
- Connected for the future using LAN and WiFi

EAN: 4002516544586 / Material number: 12012110 /  
Old Material Number: 52914017NAM

### Construction type and design

Design	Front loader
Linie	Performance Plus
Front	Stainless Steel
Load size with a load ratio of 1:25	23 (10.0)
Load size with a load ratio of 1:18	30 (13.5)
Drum volume in ft <sup>3</sup> (l)	8.83 (250.00)
Drying system	Exhaust air
Door opening [Ø] in in.(mm)	20 1/2 (520)
Door opening angle in degrees	180
Door hinging	left
Convertible hinging	•
Stainless steel honeycomb drum	Yes

### Application

Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas and fit ness centers	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemical industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks and holiday complexes	•
Suitable for public/community care facilities	•

### Performance data

Maximum evaporation capacity in l/hour and gal. qts./hour	13 (13) gal (US)/min (l)
Specific energy consumption in kWh/kg and kWh/p	0.52
Program cycle in min.	24
Tested operating hours	20000

### Control

Control system	M Touch Pro
Programmability	programmable
Program controls	Residual moisture controlled
Max. delay start in h	24
Countdown indicator	•
Program sequence indicator	•
Choice of display language	•

### Standard electrical connection

Type of heating	Electric
Electrical connection	208/240 V 60 HZ 3 PH
Electric heater rating in kW	14.70

## PDR 914 [EL]

Professional vented dryer, electric heating

with programmable M Touch Pro controls for the maximum in flexibility.



EAN: 4002516544586 / Material number: 12012110 /

Old Material Number: 52914017NAM

Total connected load in kW	15.30
Fuse rating in A	50

### Dimensions and weight of dryer

External dimensions, net height in inches	55 1/8 (1400)
External dimensions, net width in inches	35 11/16 (906)
External dimensions, net depth in inches	33 9/16 (852)
External dimensions, gross height in inches	60 1/8 (1526)
External dimensions, gross width in inches	42 15/16 (1090)
External dimensions, gross depth in inches	36 15/16 (938)
Net weight in lbs. (kg)	354 (160.4)
Gross weight in lbs. (kg)	380 (172)
Maximum floor load in N	2024

### Emission values

Emissions – sound pressure at workplace	51 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	3.90

### Features

Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecycling	•
Communication slot	•
Program selection via color frame	•
Emergency shut off	•
Machine-independent accessories	•

### Efficiency and sustainability

Recycling rate in %	92
---------------------	----

### Connection options

Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
Wi-Fi	•
Connector Box	•
LAN module (optional)	•

### Capacities

Respirator masks [number]	8
Standard and target group programs	1
Over jackets [number]	2
Synthetic duvets [number]	1
Synthetic pillows [number]	2
Feather duvets [number]	1
Feather pillows [number]	2
Cloths, 22 g/0.8 oz [number]	255
Cotton mops, 40 cm [number]	53
Cotton mops, 50 cm [number]	45
Microfibre mops, 40 cm [number]	83
Microfibre mops, 50 cm [number]	59

PDR 914 [EL]  
Professional vented dryer, electric heating  
with programmable M Touch Pro controls for the maximum in flexibility.



EAN: 4002516544586 / Material number: 12012110 /  
Old Material Number: 52914017NAM

Summer horse blankets [number]	2
<b>Standards, test certificates, and symbols</b>	
Splash-proof safety rating IPX4	•
c ETL US	•
Complies with Machinery Directive 2006/42/EC	•