



- Drum volume 8.48 (240) ft<sup>3</sup> (l), load size 55 (24.5) lb (kg)
- Large program variety application-specific wash programs
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 43 %<sup>\*</sup>, g-factor541

Residual moisture specification relates to a hot rinse during the last rinse cycle.

Construction type and design    Front loader      Product line    Front loader      Product line    Professional      Front    Stainless Steel      Control panel color    Stainless Steel      Load ratio    1:10      Load ratio    1:10      Load in lbs    55 (24.5)      Drum volume in cubic feet (I)    8.48 (240)      Door opening [2] in in.(mm)    16 15/16 (430)      Door opening angle in degrees    180      Door opening angle in degrees    180      Door hinging    right      Maintenance-free motor with frequency converter    •      Honeycomb drum    •      Application    Suitable for the hotel and catering industry      Suitable for facility management    •      Suitable for dry cleaners    •      Suitable for dry cleaners    •      Suitable for sports clubs    •      Suitable for sports
Product line  Professional    Front  Stainless Steel    Control panel color  Stainless Steel    Load ratio  1:10    Load ratio  1:10    Load in lbs  55 (24.5)    Drum volume in cubic feet (I)  8.48 (240)    Door opening [Ø] in in.(mm)  16 15/16 (430)    Door opening angle in degrees  180    Door thinging  right    Maintenance-free motor with frequency converter  •    Honeycomb drum  •    Application  Suitable for the hotel and catering industry    Suitable for facility management  •    Suitable for dry cleaners  •    Suitable for dry cleaners  •    Suitable for sports clubs  •
Control panel color  Stainless Steel    Load ratio  1:10    Load in Ibs  55 (24.5)    Drum volume in cubic feet (I)  8.48 (240)    Door opening [Ø] in in.(mm)  16 15/16 (430)    Door opening angle in degrees  180    Door hinging  right    Maintenance-free motor with frequency converter  •    Honeycomb drum  •    Application  •    Suitable for senior living facilities  •    Suitable for facility management  •    Suitable for dry cleaners  •    Suitable for dry cleaners  •    Suitable for onwnercial laundries  •    Suitable for nownercial laundries  •    Suitable for sports clubs  •    Suitable for consumption for cold water con
Load ratio1:10Load in Ibs55 (24.5)Drum volume in cubic feet (I)8.48 (240)Door opening [Ø] in in.(mm)16 15/16 (430)Door opening angle in degrees180Door hingingrightMaintenance-free motor with frequency converter•Honeycomb drum•Application•Suitable for senior living facilities•Suitable for dry cleaners•Suitable for dry cleaners•Suitable for fire brigades and rescue services•Suitable for sports clubs•Suitable for hospitals•Suitable for orsports clubs•Suitable for onsports clubs•Suitable for consumption for cold water connection in RM/h/b•Performance data•Tested vincidal efficacy•Proven hygiene•Specific energy consumption for cold water connection in RM/h/b0.10Whr/lb•Water consumption for hot water connection in NMN6.24Energy consumption for cold water connection in Mops6.56
Load ratio1:10Load in Ibs55 (24.5)Drum volume in cubic feet (I)8.48 (240)Door opening [Ø] in in.(mm)16 15/16 (430)Door opening angle in degrees180Door hingingrightMaintenance-free motor with frequency converter•Honeycomb drum•Application•Suitable for senior living facilities•Suitable for dry cleaners•Suitable for dry cleaners•Suitable for fire brigades and rescue services•Suitable for sports clubs•Suitable for hospitals•Suitable for orsports clubs•Suitable for onsports clubs•Suitable for consumption for cold water connection in RM/h/b•Performance data•Tested vincidal efficacy•Proven hygiene•Specific energy consumption for cold water connection in RM/h/b0.10Whr/lb•Water consumption for hot water connection in NMN6.24Energy consumption for cold water connection in Mops6.56
Drum volume in cubic feet (I)  8.48 (240)    Door opening [Ø] in in.(mm)  16 15/16 (430)    Door opening angle in degrees  180    Door hinging  right    Maintenance-free motor with frequency converter  •    Honeycomb drum  •    Application  •    Suitable for the hotel and catering industry  •    Suitable for senior living facilities  •    Suitable for facility management  •    Suitable for dry cleaners  •    Suitable for studs, riding schools and stables  •    Suitable for sports clubs  •    Suitable for hospitals  •    Suitable for sports clubs  •    Suitable for bospitals  •    Suitable for sports clubs  •    Suitable for bospitals  •
Drum volume in cubic feet (I)  8.48 (240)    Door opening [Ø] in in.(mm)  16 15/16 (430)    Door opening angle in degrees  180    Door hinging  right    Maintenance-free motor with frequency converter  •    Honeycomb drum  •    Application  •    Suitable for the hotel and catering industry  •    Suitable for senior living facilities  •    Suitable for facility management  •    Suitable for dry cleaners  •    Suitable for studs, riding schools and stables  •    Suitable for sports clubs  •    Suitable for hospitals  •    Suitable for sports clubs  •    Suitable for bospitals  •    Suitable for sports clubs  •    Suitable for bospitals  •
Door opening [Ø] in in.(mm)  16 15/16 (430)    Door opening angle in degrees  180    Door hinging  right    Maintenance-free motor with frequency converter  •    Honeycomb drum  •    Application  •    Suitable for the hotel and catering industry  •    Suitable for senior living facilities  •    Suitable for facility management  •    Suitable for commercial laundries  •    Suitable for studs, riding schools and stables  •    Suitable for sports clubs  •    Suitable for poptials  •    Suitable for sports clubs  •    Suitable for poptisclus  •    Suitable for sports clubs  •    Suitable for sports clubs  •    Suitable for bray class, spas, and fitness centers  •    Performance data  •    Tested virucidal efficacy  •    Proven hygiene  9.00    Specific water consumption for cold water connection in l/kg  8.80    Specific water consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kt/lb  0.10
Door opening angle in degrees  180    Door hinging  right    Maintenance-free motor with frequency converter  •    Honeycomb drum  •    Application  •    Suitable for the hotel and catering industry  •    Suitable for senior living facilities  •    Suitable for facility management  •    Suitable for dry cleaners  •    Suitable for ocommercial laundries  •    Suitable for studs, riding schools and stables  •    Suitable for hospitals  •    Suitable for hospitals  •    Suitable for sports clubs  •    Suitable for beauty salons, spas, and fitness centers  •    Performance data  •    Tested virucidal efficacy  •    Proven hygiene  •    Specific water consumption for cold water connection in gal/lb  0.26    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  6.24    Energy consumption for cold water connection in kWh (b.24  6.56
Door hinging  right    Maintenance-free motor with frequency converter  •    Honeycomb drum  •    Application  •    Suitable for the hotel and catering industry  •    Suitable for senior living facilities  •    Suitable for facility management  •    Suitable for dry cleaners  •    Suitable for free brigades and rescue services  •    Suitable for studs, riding schools and stables  •    Suitable for hospitals  •    Suitable for sports clubs  •    Suitable for beauty salons, spas, and fitness centers  •    Specific water consumption for cold water connection in gal/lb  9.00    Specific energy consumption for cold water connection in l/kg  8.80    Specific water consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  0.10    Wh/lb  Water consumption for cold water connection in l  216.0    Energy consumption for cold water connection in kWh (b c.24  Energy consumption for cold water connection in kWh
Maintenance-free motor with frequency converter  •    Honeycomb drum  •    Application  •    Suitable for the hotel and catering industry  •    Suitable for senior living facilities  •    Suitable for facility management  •    Suitable for dry cleaners  •    Suitable for commercial laundries  •    Suitable for studs, riding schools and stables  •    Suitable for nospitals  •    Suitable for sports clubs  •    Suitable for sports clubs  •    Suitable for beauty salons, spas, and fitness centers  •    Performance data  •    Tested virucidal efficacy  •    Proven hygiene  •    Specific water consumption for cold water connection in gal/b  0.26    Specific water consumption for hot water connection in I/kg  8.80    Specific energy consumption for hot water connection in I/kg  8.80    Specific energy consumption for cold water connection in I/kg  8.80    Specific energy consumption for cold water connection in I  216.0    Energy consumption for cold water connection in KWh  6.24    Energy consumption for cold water
Honeycomb drum  •    Application  •    Suitable for the hotel and catering industry  •    Suitable for senior living facilities  •    Suitable for senior living facilities  •    Suitable for facility management  •    Suitable for dry cleaners  •    Suitable for orommercial laundries  •    Suitable for studs, riding schools and stables  •    Suitable for studs, riding schools and stables  •    Suitable for nospitals  •    Suitable for hospitals  •    Suitable for sports clubs  •    Suitable for beauty salons, spas, and fitness centers  •    Performance data  •    Tested virucidal efficacy  •    Proven hygiene  •    Specific water consumption for cold water connection in gal/b  0.26    Specific energy consumption for hot water connection in I/kg  8.80    Specific energy consumption for hot water connection in I/kg  8.80    Specific energy consumption for hot water connection in I  216.0    Energy consumption for cold water connection in KWh  6.24    Energy consumption for cold water connection in Mops
ApplicationSuitable for the hotel and catering industrySuitable for senior living facilitiesSuitable for senior living facilitiesSuitable for dry cleanersSuitable for dry cleanersSuitable for commercial laundriesSuitable for studs, riding schools and stablesSuitable for niversities, nurseries, and schoolsSuitable for studs, riding schools and stablesSuitable for niversities, nurseries, and schoolsSuitable for sports clubsSuitable for sports clubsSuitable for beauty salons, spas, and fitness centersPerformance dataTested virucidal efficacyProven hygieneSpecific energy consumption for cold water connection in kWh/lbSpecific energy consumption for hot water connection in kWh/lbSpecific energy consumption for hot water connection in kWh/lbWater consumption for cold water connection in kWh/lbWater consumption for cold water connection in kWh/lbSpecific energy consumption for cold water connection in kWh/lbSpecific energy consumption for cold water connection in kWh/lbWater consumption for cold water connection in kWh/lbMater consumption for cold water connection in l kWh/lbEnergy consumption for cold water connection in kWh 6.24Energy consumption for cold water connection in Mops6.56
Suitable for the hotel and catering industry  •    Suitable for senior living facilities  •    Suitable for facility management  •    Suitable for dry cleaners  •    Suitable for commercial laundries  •    Suitable for studs, riding schools and stables  •    Suitable for niversities, nurseries, and schools  •    Suitable for nospitals  •    Suitable for sports clubs  •    Suitable for beauty salons, spas, and fitness centers  •    Performance data  •    Tested virucidal efficacy  •    Proven hygiene  •    Specific energy consumption for cold water connection in gal/lb  9.00    Specific water consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kWh/lb  216.0    Water consumption for cold water connection in l  216.0    Energy consumption for cold water connection in kWh  6.24
Suitable for senior living facilities•Suitable for facility management•Suitable for dry cleaners•Suitable for commercial laundries•Suitable for fire brigades and rescue services•Suitable for studs, riding schools and stables•Suitable for universities, nurseries, and schools•Suitable for sports clubs•Suitable for beauty salons, spas, and fitness centers•Performance data•Tested virucidal efficacy•Proven hygiene•Specific energy consumption for cold water connection in kWh/lb0.26Specific energy consumption for hot water connection in kWh/lb0.10Water consumption for cold water connection in kWh/lb216.0Energy consumption for cold water connection in l kWh/lb216.0Energy consumption for cold water connection in Mops6.56
Suitable for facility management•Suitable for dry cleaners•Suitable for ory cleaners•Suitable for commercial laundries•Suitable for fire brigades and rescue services•Suitable for studs, riding schools and stables•Suitable for universities, nurseries, and schools•Suitable for hospitals•Suitable for sports clubs•Suitable for beauty salons, spas, and fitness centers•Performance data•Tested virucidal efficacy•Proven hygiene•Specific energy consumption for cold water connection in kWh/lb0.26Specific energy consumption for hot water connection in kWh/lb0.10Water consumption for cold water connection in kWh/lb0.10Water consumption for cold water connection in kWh/lb216.0Energy consumption for cold water connection in KWh6.24Energy consumption for cold water connection in Mops6.56
Suitable for dry cleaners  •    Suitable for commercial laundries  •    Suitable for fire brigades and rescue services  •    Suitable for studs, riding schools and stables  •    Suitable for universities, nurseries, and schools  •    Suitable for hospitals  •    Suitable for sports clubs  •    Suitable for beauty salons, spas, and fitness centers  •    Performance data  •    Tested virucidal efficacy  •    Proven hygiene  •    Specific water consumption for cold water connection in gal/lb  9.00    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for cold water connection in l  216.0    Energy consumption for cold water connection in kWh  6.24    Energy consumption for cold water connection in Mops  6.56
Suitable for commercial laundries•Suitable for fire brigades and rescue services•Suitable for studs, riding schools and stables•Suitable for universities, nurseries, and schools•Suitable for hospitals•Suitable for sports clubs•Suitable for beauty salons, spas, and fitness centers•Performance data•Tested virucidal efficacy•Proven hygiene•Specific water consumption for cold water connection in gal/b0.26Specific water consumption for hot water connection in l/kg8.80Specific energy consumption for hot water connection in kWh/lb0.10Water consumption for cold water connection in l216.0Energy consumption for cold water connection in kWh6.24Energy consumption for cold water connection in Mops6.56
Suitable for studs, riding schools and stables•Suitable for universities, nurseries, and schools•Suitable for hospitals•Suitable for sports clubs•Suitable for beauty salons, spas, and fitness centers•Performance data•Tested virucidal efficacy•Proven hygiene•Specific water consumption for cold water connection in gal/lb9.00Specific energy consumption for cold water connection in kWh/lb0.26Specific energy consumption for hot water connection in kWh/lb0.10Water consumption for cold water connection in kWh/lb216.0Energy consumption for cold water connection in kWh lb6.24Energy consumption for cold water connection in Mops6.56
Suitable for studs, riding schools and stables•Suitable for universities, nurseries, and schools•Suitable for hospitals•Suitable for sports clubs•Suitable for beauty salons, spas, and fitness centers•Performance data•Tested virucidal efficacy•Proven hygiene•Specific water consumption for cold water connection in gal/lb9.00Specific energy consumption for cold water connection in kWh/lb0.26Specific energy consumption for hot water connection in kWh/lb0.10Water consumption for cold water connection in kWh/lb216.0Energy consumption for cold water connection in kWh lb6.24Energy consumption for cold water connection in Mops6.56
Suitable for universities, nurseries, and schools  •    Suitable for hospitals  •    Suitable for sports clubs  •    Suitable for beauty salons, spas, and fitness centers  •    Performance data  •    Tested virucidal efficacy  •    Proven hygiene  •    Specific water consumption for cold water connection in gal/lb  9.00    Specific energy consumption for cold water connection in kWh/lb  0.26    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for cold water connection in l/kg  8.80    Specific energy consumption for cold water connection in l/kg  8.80    Specific energy consumption for cold water connection in l  0.10    kWh/lb  0.10  10    Water consumption for cold water connection in l  216.0    Energy consumption for cold water connection in kWh  6.24    Energy consumption for cold water connection in Mops  6.56
Suitable for hospitals•Suitable for sports clubs•Suitable for beauty salons, spas, and fitness centers•Performance data•Tested virucidal efficacy•Proven hygiene•Specific water consumption for cold water connection in gal/lb9.00Specific energy consumption for cold water connection in kWh/lb0.26Specific water consumption for hot water connection in I/kg kWh/lb8.80Specific energy consumption for hot water connection in kWh/lb0.10Water consumption for cold water connection in I216.0Energy consumption for cold water connection in KWh6.24Energy consumption for cold water connection in Mops6.56
Suitable for sports clubs  •    Suitable for beauty salons, spas, and fitness centers  •    Performance data  •    Tested virucidal efficacy  •    Proven hygiene  •    Specific water consumption for cold water connection in gal/lb  9.00    Specific energy consumption for cold water connection in kWh/lb  0.26    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in 0.10  0.10    kWh/lb  216.0    Energy consumption for cold water connection in kWh  6.24    Energy consumption for cold water connection in Mops  6.56
Suitable for beauty salons, spas, and fitness centers  •    Performance data  •    Tested virucidal efficacy  •    Proven hygiene  •    Specific water consumption for cold water connection in gal/lb  9.00    Specific energy consumption for cold water connection in kWh/lb  0.26    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for cold water connection in l/kg  8.80    Specific onergy consumption for cold water connection in l/kg  8.80    Specific energy consumption for cold water connection in l  0.10    kWh/lb  Energy consumption for cold water connection in kWh  6.24    Energy consumption for cold water connection in Mops  6.56
Performance data    Tested virucidal efficacy    Proven hygiene    Specific water consumption for cold water connection in gal/lb    Specific energy consumption for cold water connection in kWh/lb    Specific water consumption for hot water connection in l/kg    Specific energy consumption for hot water connection in l/kg    Specific energy consumption for hot water connection in l/kg    Water consumption for cold water connection in l    Water consumption for cold water connection in l    Energy consumption for cold water connection in kWh    6.24    Energy consumption for cold water connection in Mops
Tested virucidal efficacy  •    Proven hygiene  •    Specific water consumption for cold water connection in gal/b  9.00    Specific energy consumption for cold water connection in kWh/lb  0.26    Specific water consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in 0.10  0.10    WWh/lb  0.10    Water consumption for cold water connection in 1  216.0    Energy consumption for cold water connection in kWh  6.24    Energy consumption for cold water connection in Mops  6.56
Proven hygiene  •    Specific water consumption for cold water connection in gal/b  9.00    Specific energy consumption for cold water connection in kWh/lb  0.26    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in 0.10  0.10    WMh/lb  216.0    Energy consumption for cold water connection in kWh  6.24    Energy consumption for cold water connection in Mops  6.56
Specific water consumption for cold water connection in gal/lb  9.00    Specific energy consumption for cold water connection in kWh/lb  0.26    Specific water consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  8.80    Specific energy consumption for cold water connection in l  0.10    kWh/lb  216.0    Energy consumption for cold water connection in kWh  6.24    Energy consumption for cold water connection in Mops  6.56
Specific energy consumption for cold water connection in  0.26    kWh/lb  Specific water consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in  0.10    kWh/lb  0.10    Water consumption for cold water connection in l  216.0    Energy consumption for cold water connection in kWh  6.24    Energy consumption for cold water connection in Mops  6.56
kWh/lb  Specific water consumption for hot water connection in l/kg  8.80    Specific energy consumption for hot water connection in l/kg  0.10    kWh/lb  0.10    Water consumption for cold water connection in l  216.0    Energy consumption for cold water connection in kWh  6.24    Energy consumption for cold water connection in Mops  6.56
Specific energy consumption for hot water connection in kWh/lb0.10Water consumption for cold water connection in I216.0Energy consumption for cold water connection in kWh6.24Energy consumption for cold water connection in Mops6.56
kWh/lb216.0Water consumption for cold water connection in I216.0Energy consumption for cold water connection in kWh6.24Energy consumption for cold water connection in Mops6.56
Energy consumption for cold water connection in kWh6.24Energy consumption for cold water connection in Mops6.56
Energy consumption for cold water connection in Mops 6.56
standard program in kWh
Program duration in minutes with cold water connection 60
Water consumption for hot water connection in I 211.0
Water consumption for hot water connection in Mops 276.1
standard program in gal
Energy consumption for hot water connection in kW 2.40
Energy consumption for hot water connection in Mops 1.66 standard program in kWh
Program duration in minutes with hot water connection 49
Water consumption in ECO program for cold water212.3connection in I
Energy consumption in ECO program for cold water  5.04    connection in kWh





Program duration in minutes for ECO program with cold	46
water connection Water consumption in ECO program for hot water connection in I	212.5
Energy consumption in ECO program for hot water connection in kWh	1.44
Program duration in minutes for ECO program with hot water connection	36
Program runtime in minutes for Mops standard program with cold water connection	74
Program runtime in minutes for Mops standard program with hot water connection	57
Residual moisture with cold rinse in %	46
Residual moisture with hot rinse in %	43
Residual moisture when processing cleaning cloths in %	25
Spin speed in rpm	1100
g factor	541
Tested operating hours	30000
Control	
Control system	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Can be selected freely
Countdown indicator	•
Program sequence indicator	•
Choice of display language	•
Standard/target group programs	
Basic programmes	•
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	•
Programmes for facility management	•
Programmes for dry cleaners	•
Programmes for small businesses	•
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	•
Programmes for hospitals	
Programmes for sports clubs	•
Programmes for beauty clinics, spas, and fitness studios	•
Dispensing	-
Detergent dispenser drawer	3 compartments
Liquid dispensing module	•
Maximum number of connections for liquid dispenser	12
pumps [number]	12
Empty sensor	•
Standard electrical connection	
Type of heating	Electric
Electrical connection	208/240 V 60 HZ 3 PH
Heater rating in kW	24.60
Total connected load in kW	26.20
Fuse rating in A	70
Water connection/drainage	
Cold water [number]	3 x 1/2" hose w/ 3/4" union
	0 X 1/2 11030 W/ 0/4 UHIUH



Hot water [number]	1x 1/2" hose w/ 3/4" th. union DN 70
Dimensions and weight	64 10/16 (1646)
External dimensions, net height in inches	64 13/16 (1646)
External dimensions, net width in inches	42 7/8 (1089)
External dimensions, net depth in inches	51 9/16 (1309)
External dimensions, gross height in inches	67 3/8 (1710)
External dimensions, gross width in inches	49 11/16 (1262)
External dimensions, gross depth in inches	58 (1472)
Net weight in Ibs.(kg)	1517 (688.0)
Gross weight in lbs.	1630 (739)
Maximum floor load in N/m <sup>2</sup>	9324
Emission values	
Emissions – sound pressure at workplace	73 dB(A) re 20 µPa
Heat dissipation into the room in BTU/h	4.70
Features	
Patented preliminary drainage	•
Patented cleaning cloth program	•
Imbalance monitoring	•
Temperature monitoring	•
Special heater element	•
Automatic load control Plus	•
Volumetric flow meter (optional)	•
Communication slot	•
Emergency shut off	•
Appliance-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	96
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Serial interface module RS 232 (optional)	•
Peak-load negotiation/energy management (optional)	•
Logging operating data	•
Water recovery (optional)	•
Capacities	
Respirator masks [number]	20
Helmets [number]	6
Overalls [number]	4
Over jackets [number]	6
Chemical protection overalls [number]	2
Synthetic duvets [number]	2
Synthetic pillows [number]	4
Feather duvets [number]	2
Feather pillows [number]	4
Cloths, 22 g/0.8 oz[number]	578
Cotton mops, 40 cm/15.7 in[number]	126
Cotton mops, 50 cm/19.7 in[number]	112
Microfibre mops, 40 cm/15.7 in [number]]	223
Microfibre mops, 50 cm/19.7 in [number]	146





Mops, office, 100 g [quantity]	233
Mops, stairway, 150 g [quantity]	155
Summer horse blankets [number]	4
Standards, test certificates, and symbols	
Splash protection IPX4	•
c ETL US	•
Complies with Machinery Directive 2006/42/EC	•