



- Drum volume 11.3 (320) ft³ (I), load size 75 (34.0) lb (kg)
- Large program variety applicationspecific wash programs
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 47 %^{*}, g-factor447

* Residual moisture specification relates to a hot rinse during the last rinse cycle.

EAN: 4002516584834 / Material number: 12088690 /
Old Material Number: 51632187NAM

Construction type and design	
Design	Front loader
Product line	Professional
Front	Stainless Steel
Control panel color	Stainless Steel
Load ratio	1:10
Load in lbs	75 (34.0)
Drum volume in cubic feet (I)	11.3 (320)
Door opening [Ø] in in.(mm)	16 15/16 (430)
Door opening angle in degrees	180
Door hinging	right
Maintenance-free motor with frequency converter	•
Stainless steel honeycomb drum	•
Application	
Suitable for hotels and restaurants	•
Suitable for senior living facilities	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centers	•
Suitable for the petrochemical industry	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in $\ensuremath{I}/\ensuremath{kg}$	9.00
Specific energy consumption for cold water connection in kWh/lb	0.25
Specific water consumption for hot water connection in I/kg	8.80
Specific energy consumption for hot water connection in kWh/lb	0.10
Water consumption for cold water connection in l	288.0
Energy consumption for cold water connection in kWh	8.00
Energy consumption for cold water connection in Mops standard program in kWh	8.74
Program duration in minutes with cold water connection	58
Water consumption for hot water connection in I	281.6
Water consumption for hot water connection in Mops standard program in gal	368.1
Energy consumption for hot water connection in kW	3.20
Energy consumption for hot water connection in Mops standard program in kWh	2.21
Program duration in minutes with hot water connection	49





EAN: 4002516584834 / Material number: 12088690 / Dld Material Number: 51632187NAM	
Water consumption in ECO program for cold water connection in I	281.6
Energy consumption in ECO program for cold water connection in kWh	6.20
Program duration in minutes for ECO program with cold water connection	54
Water consumption in ECO program for hot water connection in I	284.8
Energy consumption in ECO program for hot water connection in kWh	1.60
Program duration in minutes for ECO program with hot water connection	39
Program runtime in minutes for Mops standard program with cold water connection	70
Program runtime in minutes for Mops standard program with hot water connection	55
Residual moisture with cold rinse in %	50
Residual moisture with hot rinse in $\%$	47
Residual moisture when processing cleaning cloths in $\%$	25
Spin speed in rpm	1000
g factor	447
Tested operating hours	30000
Control	
Control system	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Can be selected freely
Countdown indicator	•
Program sequence indicator	•
Choice of display language	•
Option to enter weight prior to start of program	•
Standard/target group programs	
Basic programmes	•
Dispensing	
Detergent dispenser drawer	3 compartments
Liquid dispensing module	•
Maximum number of connections for liquid dispenser pumps [number]	12
Empty sensor	•
Standard electrical connection	
	In alter at a tax and
Type of heating	Indirect steam
Electrical connection	
Electrical connection Steam heater rating in kW	208/240 V 60 HZ 3 PH
Electrical connection Steam heater rating in kW Total connected load in kW	208/240 V 60 HZ 3 PH 50.00
Electrical connection Steam heater rating in kW Total connected load in kW Fuse rating in A	208/240 V 60 HZ 3 PH 50.00 4.40
Type of heating Electrical connection Steam heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]	208/240 V 60 HZ 3 PH 50.00 4.40
Electrical connection Steam heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage	208/240 V 60 HZ 3 PH 50.00 4.40 15 3 x 1/2" hose w/ 3/4"



EAN: 4002516584834 / Material number: 12088690 / Old Material Number: 51632187NAM Steam connection Steam connection 2 x 1/2" Dimensions and weight External dimensions, net height in inches 64 13/16 (1646) External dimensions, net width in inches 42 7/8 (1089) External dimensions, net depth in inches 51 9/16 (1309) External dimensions, gross height in inches 67 3/8 (1710) External dimensions, gross width in inches 49 11/16 (1262) External dimensions, gross depth in inches 58 (1472) Net weight in lbs.(kg) 1539 (698.0) 1652 (749) Gross weight in lbs. Maximum floor load in N 9697 **Emission values** Emissions - sound pressure at workplace 73 dB(A) re 20 µPa Heat dissipation into the room in MJ/h 6.10 Features Patented preliminary drainage ٠ Patented cleaning cloth program ٠ Imbalance monitoring ٠ Temperature monitoring Automatic load control Plus • Volumetric flow meter (optional) ٠ Communication slot • Efficient fast spin cycle • Emergency shut off ٠ Appliance-independent accessories ٠ Efficiency and sustainability 96 Recycling rate in % **Connection options** Payment system (optional) . Optical interface for service access . Serial interface module RS 232 (optional) • Peak-load negotiation / energy management (optional) • Logging operating data ٠ Water recovery (optional) • Capacities Respirator masks [number] 26 8 Helmets [number] 4 Overalls [number] Over jackets [number] 9 Chemical protection overalls [number] 2 2 Synthetic duvets [number] Synthetic pillows [number] 6 Feather duvets [number] 2 Feather pillows [number] 6 710 Cloths, 22 g/0.8 oz[number] Cotton mops, 40 cm/15.7 in[number] 168 Cotton mops, 50 cm/19.7 in[number] 142





EAN: 4002516584834 / Material number: 12088690 , Old Material Number: 51632187NAM	/	
Microfibre mops, 40 cm/15.7 in [number]]	297	
Microfibre mops, 50 cm/19.7 in [number]	180	
Mops, office, 100 g [quantity]	320	
Mops, stairway, 150 g [quantity]	210	
Summer horse blankets [number]	6	
Standards, test certificates, and symbols		
Splash protection IPX4	•	
c ETL US	•	
Complies with Machinery Directive 2006/42/EC	•	