

## PWA 8672 [U DS5 2AC208V/60HZ]

### Washer

With liquid dispensing and AutoOpen function.



- Shortest program runtime: 25 min
- Capacity/cycle: e.g., up to 24 medium sized cassettes
- Performance/cycle: e.g., 12 Large sized Cassettes, 24 medium sized cassettes
- Maximum user convenience with M Touch Flex full-touch color display
- Connectivity as standard via Wi-Fi

EAN: 4002516884781 / Material number: 12800830 /  
Old Material Number: 62867202NAM

#### Construction type and design

Model	Freestanding appliance, can be built-under, slim
Line	ExploreLine
Control panel color	Black
Outer casing	Stainless Steel
Can be built-under	•
lid	Without lid
Number of wash levels	2
AutoClose – Automatic door lock	•
Buzzer, acoustic signal at end of program	•
Easy-to-service construction	•

#### Application

Suitable for dentist's offices	•
--------------------------------	---

#### Capacity

Surgical saliva extractors per cycle [number]	44
Lumened instruments per cycle [number]	44
Transmission instruments per cycle [number]	44
Medium Cassettes (8x6")	18
Large Cassettes (8x11")	18

#### Performance data

Circulation pump, Qmax in gal/min (l/min)	132.1 (500)
Usable wash cabinet volume in l	5.12 (145.00)
Shortest program cycle time (cleaning and disinfection) in min.	25
Tested operating hours	15000
Maximum final rinse temperature in °F (in °C)	158 (70)

#### Miele MOVE

Miele MOVE Connect (option)	•
-----------------------------	---

#### Control

Control system	M Touch Flex
Cycle approval directly via the display	•
Max. delay start in h	24
Programmability	programmable
Programs [number]	5
Free program slots [number]	5
Time-left display	•
Program-cycle display	•
Choice of display languages	•

#### Standard electrical connection

Electrical connection	2 AC 208V 60HZ
Electric heater rating in kW	5.40
Total rated load in kW	6.20
Fuse rating in A	30
Length of power cord in ft (m)	6 (1.90)

#### Possible voltage variant 1

Electrical connection	3 AC 208V 60HZ
Electric heater rating in kW	5.40

## PWA 8672 [U DS5 2AC208V/60HZ]

Washer

With liquid dispensing and AutoOpen function.



EAN: 4002516884781 / Material number: 12800830 /  
Old Material Number: 62867202NAM

Total rated load in kW	6.20
Fuse rating in A	20
<b>Water connection/drainage</b>	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in kPa	200-1000
Maximum delivery head for drain pump in inches (cm)	39 3/8 (100)
Maximum water hardness (cold water/hot water) in gpg (mmol/l)	62.59 (10.70)
Drain pump [DN]	0.86 (22)
Integrated water softener	•
Water protection system	Waterproof system
<b>Dimensions and weight</b>	
External dimensions, net height in inches	32 5/16 (820)
External dimensions, net width in inches	23 9/16 (598)
External dimensions, net depth in inches	23 9/16 (598)
External dimensions, gross height in inches	36 1/4 (920)
External dimensions, gross width in inches	26 7/16 (670)
External dimensions, gross depth in inches (mm)	29 3/16 (740)
Wash cabinet, usable height in inches	20 1/2 (520)
Wash cabinet, usable width in inches	20 7/8 (530)
Wash cabinet, depth of upper basket in inches	18 11/16 (474)
Net weight in lbs	149.91 (68)
Wash cabinet, depth of lower basket in inches	20 1/2 (520)
Gross weight in lbs	169.75 (77)
Maximum floor load in N/m <sup>2</sup>	1220
<b>Emission values</b>	
Emission sound pressure level in the workplace	≤70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	0.50
<b>Programs</b>	
Vario Dental	•
Vario Dental +	•
Cold water rinse	•
Clean machine	•
<b>Features</b>	
1 door dispenser for rinse aid	•
1 dispenser pump for liquid cleaning agent	•
1 dispenser pump for neutralizing agent	•
Suction wand for media canisters 10–20 L (optional)	•
Convenient suction wand DC5	•
Volume-flow control	•
Spray pressure monitoring	•
Spray arm monitoring	•
How-to sequences	•
Interface for process documentation (optional)	•
Multi-component filter system	•
Variable-speed heating pump	•
Load carrier – direct coupling	•
AutoOpen	•

PWA 8672 [U DS5 2AC208V/60HZ]

Washer

With liquid dispensing and AutoOpen function.



EAN: 4002516884781 / Material number: 12800830 /

Old Material Number: 62867202NAM

Door salt container	•
Optical interface for Customer Service	•
Wash cabinet seamlessly welded using laser technology	•
Heating elements outside the wash cabinet	•
Wash cabinet made of high-quality stainless steel (1.4301/304)	•
Extensive components (option)	•
<b>Connection options</b>	
Wi-Fi	•
Ethernet interface (optional)	•
<b>Standards, test certificates, and symbols</b>	
IP safety class according to EN 60529: IP 21	•
EN 61010-1	•
EN 61010-2-040	•
EU medical device class IIb	•
FDA, Health Canada, Medical Device class II	•