

PWA 8672 [U DS5 2AC208V/60HZ]

Washer

With liquid dispensing and AutoOpen function.



- Shortest program runtime: 25 min
- Capacity/cycle: e.g., 12 full-size cassettes (8 x 11 x 1.25 inch)
- Performance/cycle: e.g., 12 Large sized Cassettes, 24 medium sized cassettes
- Maximum user convenience with M Touch Flex full-touch color display
- Connectivity as standard via Wi-Fi

EAN: 4002516884781 / Material number: 12800830 /
Old Material Number: 62867202NAM

Construction type and design	
Model	Freestanding appliance, can be built-under, slim
Line	ExploreLine
Control panel color	Black
Outer casing	Stainless Steel
Can be built-under	•
lid	Without lid
Number of wash levels	2
AutoClose – Automatic door lock	•
Buzzer, acoustic signal at end of program	•
Easy-to-service construction	•
Application	
Suitable for dentist's offices	•
Capacity	
Surgical saliva extractors per cycle [number]	44
Lumened instruments per cycle [number]	44
Transmission instruments per cycle [number]	44
Mesh trays (30 x 176 x 273 mm) (W x H x D) per batch [number]	12
Mesh trays (41 x 176 x 273 mm) (W x H x D) per batch [number]	24
Mesh trays (38 x 152 x 246 mm) (W x H x D) per batch [number]	24
Mesh trays (32 x 203 x 279 mm) (W x H x D) per batch [number]	12
Performance data	
Circulation pump, Qmax in gal/min (l/min)	132.1 (500)
Usable wash cabinet volume in l	5.12 (145.00)
Shortest program runtime in min.	25
Tested operating hours	15000
Maximum final rinse temperature in °F (in °C)	158 (70)
Miele MOVE	
Miele MOVE Connect (option)	•
Control	
Control system	M Touch Flex
Process approval directly via the display	•
Max. delay start in h	24
Programmability	programmable
Programs [number]	5
Free program slots [number]	5
Time-left display	•
Program-cycle display	•
Choice of display languages	•
Standard electrical connection	
Electrical connection	2 AC 208V 60HZ
Electric heater rating in kW	5.40
Total rated load in kW	6.20
Fuse rating in A	30

PWA 8672 [U DS5 2AC208V/60HZ]

Washer

With liquid dispensing and AutoOpen function.



EAN: 4002516884781 / Material number: 12800830 /

Old Material Number: 62867202NAM

Length of power cord in ft (m) 6 (1.90)

Possible voltage variant 1

Electrical connection 3 AC 208V 60HZ

Electric heater rating in kW 5.40

Total rated load in kW 6.20

Fuse rating in A 20

Water connection/drainage

Cold water [number] 1

Hot water [number] 1

Required flow pressure in kPa 200-1000

Maximum delivery head for drain pump in inches (cm) 39 3/8 (100)

Maximum water hardness (cold water/hot water) in gpg (mmol/l) 62.59 (10.70)

Drain pump [DN] 0.86 (22)

Integrated water softener •

Water protection system Waterproof system

Dimensions and weight

External dimensions, net height in inches 32 5/16 (820)

External dimensions, net width in inches 23 9/16 (598)

External dimensions, net depth in inches 23 9/16 (598)

External dimensions, gross height in inches 36 1/4 (920)

External dimensions, gross width in inches 26 7/16 (670)

External dimensions, gross depth in inches (mm) 29 3/16 (740)

Wash cabinet, usable height in inches 20 1/2 (520)

Wash cabinet, usable width in inches 20 7/8 (530)

Wash cabinet, depth of upper basket in inches 18 11/16 (474)

Net weight in lbs 149.91 (68)

Wash cabinet, depth of lower basket in inches 20 1/2 (520)

Gross weight in lbs 169.75 (77)

Maximum floor load in N/m² 1220

Emission values

Emission sound pressure level in the workplace ≤70 dB(A) re 20 µPa

Heat dissipation into the room in MJ/h 0.50

Programs

Vario Dental •

Vario Dental + •

Cold water rinse •

Clean machine •

Features

1 door dispenser for rinse aid •

1 dispenser pump for liquid cleaning agent •

1 dispenser pump for neutralizing agent •

Suction wand for media canisters 10–20 L (optional) •

Convenient suction wand DC5 •

Volume-flow control •

Spray pressure monitoring •

Spray arm monitoring •

How-to sequences •

Interface for process documentation (optional) •

PWA 8672 [U DS5 2AC208V/60HZ]

Washer

With liquid dispensing and AutoOpen function.



EAN: 4002516884781 / Material number: 12800830 /

Old Material Number: 62867202NAM

Multi-component filter system	•
Variable-speed heating pump	•
Load carrier – direct coupling	•
AutoOpen	•
Door salt container	•
Optical interface for Customer Service	•
Wash cabinet seamlessly welded using laser technology	•
Heating elements outside the wash cabinet	•
Wash cabinet made of high-quality stainless steel (1.4301/304)	•
Extensive components (option)	•
Connection options	
Wi-Fi	•
Ethernet interface (optional)	•
Standards, test certificates, and symbols	
IP safety class according to EN 60529: IP 21	•
EN 61010-1	•
EN 61010-2-040	•
EU medical device class IIb	•
FDA, Health Canada, Medical Device class II	•