## Miele

## PLW 7111 [S-1044 208V]

SlimLine laboratory glassware washer, with electric heating, hot air drying. drain pump and capacitor.



- Performance/cycle 192 narrowneck glassware or 98 pipettes – 8.511 (241) ft<sup>3</sup> (I) usable capacity
- Simple and flexible SimpleLoad with flexible level positions
- Efficient high pump performance with the variable-speed pump
- High capacity reprocessing of laboratory flasks up to 13 gal

EAN: 4002516950851 / Material number: 12929080 / Old Material Number: 62711163USA

Old Material Number: 62711163USA	
Construction type and design	
Model	Freestanding appliance, 1 glass hinged door
Line	SlimLine
Heating type	Electricity
Front/back	Stainless Steel
Side panels	Stainless steel
Single/multiple installations	•
SlimLine design	•
Number of wash levels	3
Loading and unloading with telescopic runners	•
Electric door lock	•
Buzzer, acoustic signal at end of program	•
Easy-to-service construction	•
Application	
Suitable for laboratories	•
Suitable for industrial applications	•
Capacity	
Narrow-neck glassware per cycle [number]	192
Laboratory flasks per cycle [number]	108
Pipettes per cycle [number]	98
Maximum load in lb (kg)	60
Performance data	
Circulation pump, Qmax in gal/min (I/min)	198.15 (750)
Usable wash cabinet volume in L	8.51 (241)
Control	0.01 (211)
Control system	TouchControl
Program selection	Full-touch colour display
Programmability	Freely programmable
Programs [number]	23
Free program slots [number]	20
Program-cycle display	•
Choice of display languages  Standard electrical connection	•
Electrical connection	3 AC 208V 60HZ
	8.40
Heater rating in kW	
Total rated load in kW	10.00
Fuse rating in A	35
Length of power cord in ft (m)	15.74 (4.00)
Water connection/drainage	4
Cold water [number]	
Hot water [number]	
DI water [number]	1
Required flow pressure in kPa	100-600
Maximum water hardness (cold water/hot water) in gpg (mmol/l)	4.09 (0.70)
Drain pump [DN]	25



EAN: 4002516950851 / Material number: 12929080 /

## PLW 7111 [S-1044 208V]

SlimLine laboratory glassware washer, with electric heating, hot air drying. drain pump and capacitor.

Modular basket design
Chamber lighting



Old Material Number: 62711163USA Drying unit Electricity Drying unit heating type 76.52 (130) Air throughput in m<sup>3</sup>/h Time settings in 1-minute steps 0-60 HEPA-filter class H14 HEPA-filter filtration efficiency (in accordance with 99.99 DIN EN 1822) in %Electric heater rating in kW 4.00 Dimensions and weight External dimensions, net height in inches 76 7/16 (1940) in (mm) 25 5/8 (650) in (mm) External dimensions, net width in inches External dimensions, net depth in inches 27 11/16 (702) in (mm) External dimensions, gross height in inches 83 1/8 (2110) External dimensions, gross width in inches 37 1/4 (945) 33 1/8 (840) External dimensions, gross depth in inches 28 1/4 (717) Wash cabinet, height in inches 22 1/2 (570) Wash cabinet, width in inches 23 1/4 (590) Wash cabinet, depth in inches In-feed height above floor in inches 33 1/2 (850) 554 (251) Net weight in lbs 574 (260) Gross weight in lbs Maximum floor load in N/m<sup>2</sup> 680 **Emission values** Sound pressure LpA in cleaning and drying according to 68 dB(A) re 20 µPa **DIN EN ISO 11201** Heat dissipation into the room in MJ/h 0.80 **Programs** Thermal disinfection Laboratory-glassware reprocessing Plastics **Features** 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps 2 Steam condenser Volume-flow control Interface for process documentation Multi-component filter system Load carrier - direct coupling Integrated hot-air drying Miele Cloud Service SimpleLoad Wash cabinet made of high-quality stainless steel (1.4404/316L), electropolished SlimLine mobile base Variable-speed pump Multicolored chamber lighting



## PLW 7111 [S-1044 208V]

SlimLine laboratory glassware washer, with electric heating, hot air drying. drain pump and capacitor.



EAN: 4002516950851 / Material number: 12929080 / Old Material Number: 62711163USA	
Connection options	
Ethernet interface	•
WiFi	•
USB interface	*
Peak-load negotiation / energy management	•
Ctandanda tast sautificates and sauch als	
Standards, test certificates, and symbols	
CE	•
	•
CE	•
CE EN 61010-1	•
CE EN 61010-1 EN 61010-2-040	•