

PW 6080 Vario [EL LP] Washing machine, electrically heated with suspended drum unit, shortest programme running time of 53 min and drain pump.



- Drum volume 80 I, load size 8.0 kg
- Large programme variety application-specific wash programmes
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 44 %*, g-factor520

EAN: 4002514438627 / Material number: 07215260 / Old Material Number: 51608001D

| Construction type and version | |
|---|---------------------|
| Construction type | Front loader |
| Range | Octoplus |
| Front | Lotus white |
| Load ratio | 1:10 |
| Load in kg | 8,0 |
| Drum volume in I | 80 |
| Door opening [Ø] in mm | 370 |
| Door opening angle in degrees | 180 |
| Door hinge | right |
| Maintenance-free motor with frequency converter | • |
| Stainless steel honeycomb drum | • |
| Application | |
| Suitable for the hotel and catering industry | • |
| Suitable for retirement and care homes | • |
| Suitable for launderettes | • |
| Suitable for residential homes and apartments | • |
| Suitable for dry cleaners | • |
| Suitable for commercial laundries | • |
| Suitable for small businesses | • |
| Suitable for fire brigades and rescue services | • |
| Suitable for universities, nurseries, and schools | • |
| Suitable for hospitals | • |
| Suitable for camp sites | • |
| Suitable for sports clubs | • |
| Suitable for beauty salons, spas, and fitness centres | • |
| Suitable for domestic use | • |
| Suitable for doctors' and dentists' practices | • |
| Performance data | |
| Specific water consumption for hot water connection in I/kg | 8,25 |
| Specific energy consumption for hot water connection in | 0,06 |
| kWh/kg | |
| Programme duration in minutes with cold water connection | 57 |
| Programme duration in minutes with cold water and hot | 53 |
| water connection | 40 |
| Residual moisture with cold rinse in % | 49 |
| Residual moisture with hot rinse in % | 44 |
| Spin speed in rpm | 1300 |
| g factor | 520 |
| Tested operating hours | 30000 |
| Control system | |
| Control system | Profitronic L Vario |
| Programmability | programmable |
| Max. delay start in h | 24 |
| Time left display | |
| Programme sequence indicator | • |
| Selectable display languages | • |
| Standard/target grp programmes | |
| Basic programmes | • |
| Programmes for the hotel and catering industry | • |
| | - |

^{*} Residual moisture specification relates to a hot rinse during the last rinse cycle.



PW 6080 Vario [EL LP] Washing machine, electrically heated with suspended drum unit, shortest programme running time of 53 min and drain pump.



EAN: 4002514438627 / Material number: 07215260 / Old Material Number: 51608001D

| Programmes for retirement and care homes | • |
|--|--------------------------|
| Programmes for launderettes | • |
| Programmes for residential homes and apartments | • |
| Programmes for dry cleaners | • |
| Programmes for commercial laundries | • |
| Programmes for small businesses | • |
| Programmes for fire brigades and rescue services | • |
| Programmes for universities, nurseries, and school | • |
| Programmes for hospitals | • |
| Programmes for fast food restaurants | • |
| Programmes for camp sites | • |
| Programmes for sports clubs | • |
| Programmes for beauty clinics, spas, and fitness studios | • |
| Programmes for domestic use | • |
| Programmes for doctors' and dentists' practices | • |
| Dispensing | |
| Detergent drawer | 3 compartments |
| Patented liquid dispensing adapter | • |
| Maximum number of connections for liquid dispenser | 6 |
| pumps [number] | Ü |
| Empty sensor | • |
| Standard electrical connection | |
| Heating type | Electric |
| Electrical connection | 3N AC 400V 50HZ |
| Heater rating in kW | 7,95 |
| Total connected load in kW | 8,20 |
| Fuse rating in A | 16 |
| Water connection/drainage | |
| Cold water [number] | 1x 1/2" hose w/ 3/4" th. |
| | union |
| Hot water [number] | 1x 1/2" hose w/ 3/4" th. |
| | union |
| Grey water (optional) [number] | 1 x 1/2" w/ 3/4" union |
| Drain pump | DN 22 |
| Dimensions and weight | |
| External dimensions, height in mm | 1020 |
| External dimensions, width in mm | 700 |
| External dimensions, depth in mm | 727 |
| External dimensions, gross height in mm | 1215 |
| External dimensions, gross width in mm | 760 |
| External dimensions, gross depth in mm | 820 |
| Net weight in kg | 140,0 |
| Gross weight in kg | 148 |
| Maximum floor load in N/m ² | 2600 |
| Emissions data | |
| Emission sound pressure level in the workplace | <70 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h | 3,00 |
| Features | |
| Imbalance monitoring | • |
| Disinfection rinse | • |
| Temperature monitoring | • |
| | |



PW 6080 Vario [EL LP] Washing machine, electrically heated with suspended drum unit, shortest programme running time of 53 min and drain pump.



EAN: 4002514438627 / Material number: 07215260 / Old Material Number: 51608001D

| Special heater element | • |
|--|-----|
| Automatic load control | • |
| Flow meter | • |
| Communication slot | • |
| Machine-independent accessories | • |
| Efficiency and sustainability | |
| Recycling rate in % | 95 |
| Connection options | |
| Payment system | • |
| Optical interface for service access | • |
| Serial interface module RS 232 (optional) | • |
| Peak-load negotiation / energy management (optional) | • |
| Capacities | |
| Respirator masks [number] | 4-5 |
| Overalls [number] | 1 |
| Over jackets [number] | 1-2 |
| Synthetic duvets [number] | 1 |
| Synthetic pillows [number] | 1-2 |
| Down duvets [number] | 1 |
| Down pillows [number] | 1-2 |
| Standards, test certificates and symbols | |
| CE | • |
| VDE-EMC | • |
| VDE | • |
| Splash-proof safety rating IPX4 | • |
| WEEE | • |
| RCM | • |
| Complies with Machinery Directive 2006/42/EC | • |