

PT 8337 WP [PTM]

Heat-pump dryers

lowest energy consumption, without complicated exhaust ducting installation.



- Drum volume 325.00 l, load size 13.0-16.0 kg
- Unique, gentle fabric care – honeycomb drum
- Excellent energy efficiency thanks to Air Recycling Plus
- Precision drying of all fabrics – PerfectDry
- Automatic heat exchanger cleaning thanks to StreamClean process
- Fig. shows tumble dryer with heat pump module (order separately)

EAN: 4002514945200 / Material number: 07964920 / Old Material Number: 52833763ZER

Construction type and version	
Construction type	Front loader
Range	Professional
Front	Stainless steel
Load in kg	13,0-16,0
Load ratio	1:25-1:20
Drum volume in l	325,00
Drying system	Heat pump
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	Yes
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for launderettes	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Performance data	
Maximum evaporation capacity in l/hour	7,50
Programme duration in min.	54
Tested operating hours	20000
Control system	
Control system	Profitronic M
Programmability	Freely programmable
User interface	Residual moisture controlled
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard/target grp programmes	
Basic programmes	•
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	•
Programmes for facility management	•
Programmes for dry cleaners	•
Programmes for studs, riding schools, and stables	•
Standard electrical connection	
Heating type	Heat pump with CleanStream
Electrical connection	3N AC 380-415V 50HZ
Electric heater rating in kW	0,00

PT 8337 WP [PTM]

Heat-pump dryers

lowest energy consumption, without complicated exhaust ducting installation.



EAN: 4002514945200 / Material number: 07964920 / Old Material Number: 52833763ZER

Total connected load in kW	5,20
Fuse rating in A	16
Dimensions and weight	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	975
External dimensions, gross height in mm	1598
External dimensions, gross width in mm	1036
External dimensions, gross depth in mm	1196
Net weight in kg	164,0
Gross weight in kg	186
Maximum floor load in N/m ²	1870
Dimensions/weight of HP mod.	
External dimensions, net height in mm	1370
External dimensions, net width in mm	906
External dimensions, net depth in mm	426
Net weight in kg	159,5
Emissions data	
Emission sound pressure level in the workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	4,68
Features	
CleanStream (heat exchanger cleaning)	•
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
Gentle tumble function	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•
Efficiency and sustainability	
Contains fluorinated greenhouse gases	•
Hermetically sealed system	•
Coolant	R134a
Refrigerant quantity in kg	3,20
Refrigerant global warming potential in kg CO ₂ e	1430
Appliance global warming potential in kg CO ₂ e	4576
Connection options	
Payment system (optional)	•
Serial interface RS 232 (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management	•
Operating data acquisition	•
Capacities	
Respirator masks [number]	12
Overalls [number]	2
Over jackets [number]	3
Synthetic duvets [number]	1
Synthetic pillows [number]	3
Down duvets [number]	1
Down pillows [number]	3

PT 8337 WP [PTM]

Heat-pump dryers

lowest energy consumption, without complicated exhaust ducting installation.