

Octoplus Washer & Dryer For Industrial Applications

Miele Professional. Immer Besser.



Trust the Experts

In 1901, Miele designed the first ever washing machine, inspired by a butter churn. Since then, Miele has been a pioneer in the field of premium laundry care for both residential and industrial use.

Miele Professional leads the way in the research and development of innovative technology to meet the highest demands in washing, dishwashing, cleaning and disinfection. Miele is the definitive source for precision commercial cleaning equipment by combining outstanding speed, capacity and performance that's trusted by laboratories, education institutes, health care facilities and more around the world.

Miele Professional's extensive product line includes laboratory glassware washers, medical and dental washer-disinfectors, commercial dishwashers and laundry equipment.

The Ultimate Laundry Equipment

Miele's Octoplus laundry equipment is perfect for businesses who desire energy efficient commercial laundry. The 20-25 pound capacity Octoplus machines can hold 4 king sheets, 6 spa robes or 16 bath towels. Offering short cycle wash programs, high temperature disinfection and high spin extraction, the Octoplus washer and dryer provide a superior hygienic clean. In addition, Miele's Honeycomb™ drum cradles linens, towels and blankets while washing, ensuring a gentle and thorough clean while further protecting all garments.

German engineered with high performance heater elements, intelligent water intake controls and short cycle times, Octoplus machines are the ultimate tool for facilities with high throughput laundry demands.

Octoplus Laundry Equipment at a Glance

- 20-25 lbs capacity
- High temp. disinfection programs (200° F)
- High spin speed - 1300 rpms
- Patented Miele Honeycomb™ drum
- Sensor for load control
- Bearing designed for 30,000 operating hours
- Automatic detergent pumps
- Stacked units available



Miele, Inc. Princeton, NJ

800.991.9380

proinfo@mieleusa.com

www.mieleusa.com/professional

Miele


Installation Type

Machine	Washer PW 6080	Washer PW 5105	Dryer PT 7186	Dryer PT 8303	Dryer PWT 6089	Washer PWT 6089	Dryer PT 7189
Load Capacity	20 lbs	25 lbs	20 lbs	23-25 lbs	20 lbs	20 lbs	20 lbs
Machine Dimensions	27.6" W x 40.2" H x 28.7" D	27.6" W x 40.2" H x 32.6" D	27.6" W x 40.2" H x 28.7" D	27.6" W x 70.9" H x 42.9" D	27.6" W x 76" H x 30.1" D		
Drum Volume	21 gallon / 80 liter	26 gallon / 100 liter	48 gallon / 180 liter	79 gallon / 300 liter	21 gallon / 80 liter	48 gallon / 180 liter	
Drum Type	Honeycomb™ drum	Honeycomb™ drum	Honeycomb™ drum	Honeycomb™ drum	Honeycomb™ drum	Honeycomb™ drum	Honeycomb™ drum
Spin Speed	1300 rpm	1100 rpm				1300 rpm	
G-force	520	370				520	
Control Type	Profitronic L	Profitronic L	Profitronic L	Profitronic B Plus	Profitronic L Plus Vario	Profitronic L Plus Vario	Profitronic L Plus Vario
24-hour Delay Start	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Weight	310 lbs	327 lbs	167 lbs	307 lbs	298 lbs	298 lbs	165 lbs
Standard Electrical Connection	2-pole 220V-240V 60Hz (convertible to 208V)	2-pole 220V-240V 60Hz (convertible to 208V)	2-pole 208V 60Hz or 2-pole 240V 60Hz	3-pole 220V - 240V 60Hz (convertible to 3-pole 208V or 2-pole 208V)	2-pole 220V-240V 60Hz (convertible to 208V)	2-pole 220V-240V 60Hz (convertible to 208V)	2-pole 240V 60Hz or 2-pole 240V 60Hz
Standard Fuse Rating	2-pole 30 A	2-pole 30 A	2-pole 30 A	3-pole 30 A	3-pole 30 A	2-pole 30 A	2-pole 30 A
Plug Type	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	Unterminated	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P
Total Rated Load	4.0 kW at 208V or 5.2 kW at 240V	4.0 kW at 208V or 5.2 kW at 240V	4.0 kW at 208V or 5.7 kW at 240V	15.4 kW at 220-240V or 11.7 kW at 208V	4.0 kW at 208V or 5.2 kW at 240V	4.9 kW at 208V or 5.7 kW at 240V	4.9 kW at 208V or 5.7 kW at 240V
High Temperature Disinfection Programs	Yes	Yes				Yes	
Cold Water Connection	1 line, 1/2" hose with 3/4" threaded union	1 line, 1/2" hose with 3/4" threaded union				1 line, 1/2" hose with 3/4" threaded union	
Hot Water Connection	1 line, 1/2" hose with 3/4" threaded union	1 line, 1/2" hose with 3/4" threaded union				1 line, 1/2" hose with 3/4" threaded union	
Dump Valve Option	3" OD connection	3" OD connection	3" OD connection			N/A	N/A
Drain Pump Option	7/8" ID connection	N/A				7/8" ID connection	
Vent Diameter			4"	6"			4"
Dispensing Adapter for 6 Liquid Chemicals	Yes	Yes	Yes			Yes	
"Container empty" Sensors for 6 Pumps	Yes	Yes	Yes			Yes	

800.991.9380

Miele, Inc. Princeton, NJ
 proinfo@mieleusa.com www.mieleusa.com/professional